Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name of	r trade mark:	Loox5
--------------------	---------------	-------

Supplier's address: Zentrale, Adolf-Häfele-Str. 1, 72202 Nagold, DE

Model identifier: 833.74.252

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	12V Loox5 Socket		
(or other electric interface)	Socket		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers

Product parameters

Product parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
	nption in on- 00 h), rounded st integer	15	Energy efficiency class	G	
dicating if it refe a sphere (360º) (120º) or in a na	s flux (фuse), in- ers to the flux in , in a wide cone rrow cone (90º)	405 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000	
On-mode pow pressed in W	ver (P _{on}), ex-	14,4	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
(P _{net}) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90	
Outer dimen-	Height	4	Spectral power dis-	See image	
sions without	Width	1 500	tribution in the	in last page	
separate con- trol gear, light-	Depth	10	range 250 nm to 800 nm, at full-load		

ing control parts and non-lighting control parts, if any (millimetre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,458		
		nates (x and y)	0,410		
Parameters for LED and OLED light sources:					
R9 colour rendering index valu	e 50	Survival factor	0,96		
the lumen maintenance factor	0,96				

(a)'-': not applicable; (b)'-': not applicable;

